



IN-8020 / IN-8022

IN-5039 / IN-5054

XTIRPA™

XLT Fall Protection High Reach Davit System

SPECIFICATIONS

- Davit reach IN-5039: 6 ft - 1.8 m / IN-5054: 9 ft - 2.7 m
- Adjustable height IN-5039 and IN-5054:
15 ft - 4.6 m / 25 ft - 7,6 m
- Mobile solution by forklift
- Optional davit underslug rail
- Up to 2 simultaneous retrieving systems
- Optional wheeled cart system
- Easy installation with dedicated system

CERTIFICATIONS

IN-5039

ANSI Z359.18 TYPE D

AS / NZS 5532 FREEFALL

CSA Z259.15 CLASS AD

OSHA 1910.140 / 1926.502

EN 795 (2012), TS 16415 (2013)

- Type: **A, E**
- Max number of **users**: up to 3

IN-5054

AS / NZS 5532 LTD FREEFALL

OSHA 1910.140 / 1926.502

EN 795 (2012), TS 16415 (2013)

- Type: **A, E**
- Max number of **users**: up to 2



Portable with its counterweight system.



Adapter for self-retracting lifeline.



Adjustable height winch.



Horizontal trolley rail.



Handling cart for XLT system.





IN-8020 / IN-8022

IN-5039 / IN-5054

XTIRPA™

XLT The High Reach Davit

